

New Year, New Machine...?

To celebrate the start of a new decade, Sumitomo Demag have secured the following machines, available on immediate delivery:

Machine Type	Specification At a Glance	Availability	Tie Bar Distance + Max Shot Weight
All-Electric			
IntElect 50/370-110	Core Pull, Robot Interface, Dosing Device Interface, Socket Combination, Bimetallic Barrel	Immediately	370 x 370 46g (PS)
IntElect 75/420-250 x 2	Core Pull, Robot Interface, Active Flow Balance, Extended Mould Height, Dosing Device Interface, Socket Combination, Bimetallic Barrel	Immediately	420 x 420 55g (PS)
IntElect 100/470-250	Robot Interface, Socket Combination, OPC UA Interface, Active Flow Balance, Material Hopper, Pneumatic valve x 2, 6 Inputs / Outputs, Horn	Immediately	470 x 470 90g (PS)
IntElect 180/570-450	Core Pull, Robot Interface, Bimetallic Barrel, Pneumatic Valve x 2, 20mA Interface for TCU's, Increased Tie Bar Distance	Immediately	570 x 570 183g (PS)
Servo-Hydraulic			
Systec 210/580-1450	Core Pull, Robot Interface, Socket Combination, Bimetallic Barrel, Extended Mould Height, 20mA Interface for TCU's, Dosing Device Interface, 3 Inputs / Outputs	Immediately	580 x 580 695g (PS)
Systec 280/630-2300	Core Pull, Robot Interface, Socket Combination, Bimetallic Barrel, Extended Mould Height, 20mA Interface for TCU's, Dosing Device Interface, 3 Inputs / Outputs	Immediately	630 x 630 1,100g (PS)
Systec 350/720-1450	Core Pull, Robot Interface, Socket Combination, Bimetallic Barrel, Extended Mould Height, 20mA Interface for TCU's, Dosing Device Interface, 3 Inputs / Outputs	Immediately	720 x 720 695g (PS)

